



## GP45D4-A IW

This series of products used in electro-hydraulic proportional control loop control system with electro-hydraulic proportional control amplifier supporting the use, LVDT linear position sensors measuring head and the rigid connection on solenoid armature, enabling direct detection of the position of the spool, so as to achieve precise control spool displacement purposes.

✉ aykd\_scb@126.com

☎ +86-372-2595077/2595078/2595088

Free Live Chat

Leave Message

### Products

- ✦ Screw Proportional Solenoid
- ✦ Bolt Proportional Solenoid
- ✦ Servo Proportional Solenoid
- ✦ Rexroth Switch Solenoid
- ✦ Yuken Switch Solenoid
- ✦ Vickers Switch Solenoid
- ✦ Explosion-Proof Solenoid
- ✦ Waterproof Solenoid
- ✦ Position Sensor
- ✦ Displacement Transducer
- ✦ Cartridge Solenoid
- ✦ Latest Research

### Quality Assurance

- ✦ Processing Equipment
- ✦ Testing Equipment
- ✦ Quality Control

### Contact us

Tel: +86-372-2595077/2595078  
/2595088

Fax:

Email: aykd\_scb@126.com

Address: High-tech Development Zone,  
Anyang City, Henan, China



#### Description

#### Parameters

#### Related products

#### Inquiry

#### Description

##### Uses:

This series of products used in electro-hydraulic proportional control loop control system with electro-hydraulic proportional control amplifier supporting the use, LVDT linear position sensors measuring head and the rigid connection on solenoid armature, enabling direct detection of the position of the spool, so as to achieve precise control spool displacement purposes.

#### The main technical parameters:

Type	GP45D4-AIW
Specification	Φ45mm
Itinerary	3+3mm
Rated Force	80N
Coil	R2.1Ω IN2.8A
Hydraulic resistance	21MPa

#### Related products

#### Inquiry

Email: aykd\_scb@126.com

Name:

\* E-mail:

\* Content:

Send A Message