



GP45H4-GWXF004

This series of products used in a closed loop electro-hydraulic proportional control system with electro-hydraulic proportional control amplifier supporting the use, LVDT linear position sensors measuring head and the rigid connection on solenoid armature, enabling direct detection of the position of the spool, so as to achieve accurate the purpose of the control spool displacement.

aykd_scb@126.com

Free Live Chat

Leave Message

Products Screw Proportional Solenoid Bolt Proportional Solenoid Servo Proportional Solenoid · Rexroth Switch Solenoid · Yuken Switch Solenoid Vickers Switch Solenoid Explosion-Proof Solenoid Waterproof Solenoid Position Sensor Displacement Transducer Cartridge Solenoid

Quality Assurance Processing Equipment

Quality Control

Testing Equipment

Latest Research

Contact us

Tel:+86-372-2595077/2595078 /2595088

Fax:

Email:aykd_scb@126.com Address:High-tech Development Zone, Anyang City, Henan, China











■ Inquiry

Email:aykd_scb@126.com

| Description | Parameters | Related products | Inquiry | |
|----------------------------|--|-----------------------------|------------------------------------|-------|
| 1 Description | | | | |
| Jses: | | | | |
| his series of products | used in a closed loop e | lectro-hydraulic proportion | nal control system with electro-hy | ydrai |
| roportional control amp | olifier supporting the use | e, LVDT linear position | sensors measuring head and th | e ri |
| onnection on solenoid a | rmature, enabling direct d | etection of the position of | the spool, so as to achieve accur | ate t |
| ourpose of the control spo | ool displacement. | | | |
| | | | | |
| The main technical p | parameters: | | | |
| | Туре | 9 | GP45H4-GWXF004 | |
| | | | | |
| | Specification | | Φ46mm | |
| | Specification Itinerary | | Ф46mm 3+3mm | |
| | 10000000000000000000000000000000000000 | | | |
| | Itinerary | | 3+3mm | |
| Protection | Itinerary Rated Force | | 3+3mm 110N | |
| Protection | Itinerary Rated Force Coil | | 3+3mm 110N R3.2Ω IN2.6A | |
| Protection | Itinerary Rated Force Coil | | 3+3mm 110N R3.2Ω IN2.6A | |

| Name: | | | |
|----------|---------------|--|-------|
| E-mail: | | | |
| Content: | | | |
| | | | (alf) |
| s | end A Message | | |