



GP63-S-* IW63 series

This series of products used in a closed loop electro-hydraulic proportional control system with electro-hydraulic proportional control amplifier supporting the use, LVDT linear position sensors measuring head and the rigid connection on solenoid armature, enabling direct detection of the position of the spool, so as to achieve accurate the purpose of the control spool displacement.

✉ aykd_scb@126.com

☎ +86-372-2595077/2595078/2595088

Free Live Chat

Leave Message

Products

- ✦ Screw Proportional Solenoid
- ✦ Bolt Proportional Solenoid
- ✦ Servo Proportional Solenoid
- ✦ Rexroth Switch Solenoid
- ✦ Yuken Switch Solenoid
- ✦ Vickers Switch Solenoid
- ✦ Explosion-Proof Solenoid
- ✦ Waterproof Solenoid
- ✦ Position Sensor
- ✦ Displacement Transducer
- ✦ Cartridge Solenoid
- ✦ Latest Research

Quality Assurance

- ✦ Processing Equipment
- ✦ Testing Equipment
- ✦ Quality Control

Contact us

Tel: +86-372-2595077/2595078
/2595088

Fax:

Email: aykd_scb@126.com

Address: High-tech Development Zone,
Anyang City, Henan, China



Description

Parameters

Related products

Inquiry

Description

Uses:

This series of products used in a closed loop electro-hydraulic proportional control system with electro-hydraulic proportional control amplifier supporting the use, LVDT linear position sensors measuring head and the rigid connection on solenoid armature, enabling direct detection of the position of the spool, so as to achieve accurate the purpose of the control spool displacement.

The main technical parameters:

2 models	GP63-S-BIW63/GP63-S-CIW63
Specification	Φ63mm
Itinerary	4+5mm
Rated Force	150N-170N
Hydraulic resistance	21MPa
Production provided by enclosures	IP65

Related products

Inquiry

Email: aykd_scb@126.com

Name:

* E-mail:

* Content:

Send A Message