

REXROTH SOLENOID

[View Details](#)



Home > Products > Displacement Transducer >



GWEF45-004

Sensors LVDT linear position sensor, the product is no sliding contacts. With high reliability, long life and other advantages, while its high resolution, high frequency response, good repeatability and other characteristics, while products with high pressure resistance, suitable for hydraulic systems to accurately detect the position of the spool. Switch to switch displacement sensor for safety valve.

aykd_scb@126.com

+86-372-2595077/2595078/2595088

[Free Live Chat](#)

[Leave Message](#)

Products

- [Screw Proportional Solenoid](#)
- [Bolt Proportional Solenoid](#)
- [Servo Proportional Solenoid](#)
- [Rexroth Switch Solenoid](#)
- [Yuken Switch Solenoid](#)
- [Vickers Switch Solenoid](#)
- [Explosion-Proof Solenoid](#)
- [Waterproof Solenoid](#)
- [Position Sensor](#)
- [Displacement Transducer](#)
- [Cartridge Solenoid](#)
- [Latest Research](#)

Quality Assurance

- [Processing Equipment](#)
- [Testing Equipment](#)
- [Quality Control](#)

Contact us

Tel:+86-372-2595077/2595078/2595088
 Fax:
 Email:aykd_scb@126.com
 Address:High-tech Development Zone, Anyang City, Henan,China



Description	Parameters	Related products	Inquiry												
<h4>Description</h4> <p>Uses: Sensors LVDT linear position sensor, the product is no sliding contacts. With high reliability, long life and other advantages, while its high resolution, high frequency response, good repeatability and other characteristics, while products with high pressure resistance, suitable for hydraulic systems to accurately detect the position of the spool. Switch to switch displacement sensor for safety valve.</p>															
<h4>Parameters</h4> <table border="1"> <thead> <tr> <th>Type</th> <th>GWEF45-004</th> </tr> </thead> <tbody> <tr> <td>Specification</td> <td>Φ45mm</td> </tr> <tr> <td>Measurement of displacement</td> <td>±4mm</td> </tr> <tr> <td>Temperature Range</td> <td>-20°C~+80°C</td> </tr> <tr> <td>Hydraulic resistance</td> <td>31.5MPa</td> </tr> <tr> <td>Protection provided by enclosures</td> <td>IP65</td> </tr> </tbody> </table>				Type	GWEF45-004	Specification	Φ45mm	Measurement of displacement	±4mm	Temperature Range	-20°C~+80°C	Hydraulic resistance	31.5MPa	Protection provided by enclosures	IP65
Type	GWEF45-004														
Specification	Φ45mm														
Measurement of displacement	±4mm														
Temperature Range	-20°C~+80°C														
Hydraulic resistance	31.5MPa														
Protection provided by enclosures	IP65														
<h4>Related products</h4>															
<h4>Inquiry</h4> <p>Email:aykd_scb@126.com</p> <p>Name: <input type="text"/></p> <p>* E-mail: <input type="text"/></p> <p>* Content: <input type="text"/></p> <p>Send A Message</p>															

Prev Article: IW9 Series

Next Article: Switch Solenoid MFJ10A-52YC

Our News

Anyang City Vice Mayor Wang Xinwei
 My company was named the
 Anyang City Vice Mayor Du Xinjun line

About KaiDi

KAI Di Introduction
 KAI Di Sketch
 KAI Di Culture
 KAI Di Honors
 KAI Di Certification
 Download

Leave A Message

Name:

E-mail:

Content:

[Send A Message](#)

Company Information

High-tech Development Zone, Anyang City,
 Henan,China
 Tel:+86-372-2595077/2595078/2595088
 Email:aykd_scb@126.com

