

REXROTH SOLENOID

[View Details](#)



Home > Products > Displacement Transducer >



GWEF50-015

Sensors LVDT linear position sensor, the product is no sliding contacts. With high reliability, long life and other advantages, while its high resolution, high frequency response, good repeatability and other characteristics, while products with high pressure resistance, suitable for hydraulic systems to accurately detect the position of the spool. Switch to switch displacement sensor for safety valve.

aykd_scb@126.com

+86-372-2595077/2595078/2595088

[Free Live Chat](#)

[Leave Message](#)

Products

- ✦ Screw Proportional Solenoid
- ✦ Bolt Proportional Solenoid
- ✦ Servo Proportional Solenoid
- ✦ Rexroth Switch Solenoid
- ✦ Yuken Switch Solenoid
- ✦ Vickers Switch Solenoid
- ✦ Explosion-Proof Solenoid
- ✦ Waterproof Solenoid
- ✦ Position Sensor
- ✦ Displacement Transducer
- ✦ Cartridge Solenoid
- ✦ Latest Research

Quality Assurance

- ✦ Processing Equipment
- ✦ Testing Equipment
- ✦ Quality Control

Contact us

Tel:+86-372-2595077/2595078/2595088
 Fax:
Email:aykd_scb@126.com
 Address:High-tech Development Zone, Anyang City, Henan,China



Description	Parameters	Related products	Inquiry														
<p>Description</p> <p>Uses: Sensors LVDT linear position sensor, the product is no sliding contacts. With high reliability, long life and other advantages, while its high resolution, high frequency response, good repeatability and other characteristics, while products with high pressure resistance, suitable for hydraulic systems to accurately detect the position of the spool. Switch to switch displacement sensor for safety valve.</p>																	
<p>Parameters</p> <p>The main technical parameters:</p> <table border="1"> <tr> <td>Type</td> <td>GWEF50-015</td> </tr> <tr> <td>Plug</td> <td>M12*1 4-pole</td> </tr> <tr> <td>Input Voltage</td> <td>±15V</td> </tr> <tr> <td>Output Voltage</td> <td>±5V</td> </tr> <tr> <td>Hydraulic resistance</td> <td>31.5MPa</td> </tr> <tr> <td>Protection provided by enclosures</td> <td>IP67</td> </tr> <tr> <td colspan="2">The sensor has a very short response time</td> </tr> </table>				Type	GWEF50-015	Plug	M12*1 4-pole	Input Voltage	±15V	Output Voltage	±5V	Hydraulic resistance	31.5MPa	Protection provided by enclosures	IP67	The sensor has a very short response time	
Type	GWEF50-015																
Plug	M12*1 4-pole																
Input Voltage	±15V																
Output Voltage	±5V																
Hydraulic resistance	31.5MPa																
Protection provided by enclosures	IP67																
The sensor has a very short response time																	
<p>Related products</p>																	
<p>Inquiry</p> <p>Email:aykd_scb@126.com</p> <p>Name: <input type="text"/></p> <p>* E-mail: <input type="text"/></p> <p>* Content: <input type="text"/></p> <p>Send A Message</p>																	

Prev Article: Explosion-Proof Solenoid DTBZ-37FYC

Next Article: IW9 Series

Our News

Anyang City Vice Mayor Wang Xinwei
 My company was named the
 Anyang City Vice Mayor Du Xinjun line

About KaiDi

- KAI Di Introduction
- KAI Di Sketch
- KAI Di Culture
- KAI Di Honors
- KAI Di Certification
- Download

Leave A Message

Name

E-mail

Content

[Send A Message](#)

Company Information

High-tech Development Zone, Anyang City,
 Henan,China
 Tel:+86-372-2595077/2595078/2595088
 Email:aykd_scb@126.com

