

# REXROTH SOLENOID

[View Details](#)



Home > Products > Displacement Transducer >



## IW9 Series

Sensors LVDT linear position sensor, the product is no sliding contacts. With high reliability, long life and other advantages, while its high resolution, high frequency response, good repeatability and other characteristics, while products with high pressure resistance, suitable for hydraulic systems to accurately detect the position of the spool. Switch to switch displacement sensor for safety valve.

[aykd\\_scb@126.com](mailto:aykd_scb@126.com)

+86-372-2595077/2595078/2595088

[Free Live Chat](#)

[Leave Message](#)

### Products

- [Screw Proportional Solenoid](#)
- [Bolt Proportional Solenoid](#)
- [Servo Proportional Solenoid](#)
- [Rexroth Switch Solenoid](#)
- [Yuken Switch Solenoid](#)
- [Vickers Switch Solenoid](#)
- [Explosion-Proof Solenoid](#)
- [Waterproof Solenoid](#)
- [Position Sensor](#)
- [Displacement Transducer](#)
- [Cartridge Solenoid](#)
- [Latest Research](#)

### Quality Assurance

- [Processing Equipment](#)
- [Testing Equipment](#)
- [Quality Control](#)

### Contact us

Tel:+86-372-2595077/2595078/2595088  
 Fax:  
 Email:[aykd\\_scb@126.com](mailto:aykd_scb@126.com)  
 Address:High-tech Development Zone, Anyang City, Henan,China



Description	Parameters	Related products	Inquiry										
<p><b>Description</b></p> <p><b>Uses:</b> Sensors LVDT linear position sensor, the product is no sliding contacts. With high reliability, long life and other advantages, while its high resolution, high frequency response, good repeatability and other characteristics, while products with high pressure resistance, suitable for hydraulic systems to accurately detect the position of the spool. Switch to switch displacement sensor for safety valve.</p>													
<p><b>Parameters</b></p> <p>The main technical parameters:</p> <table border="1"> <tr> <td>Type</td> <td>IW9-03-01</td> </tr> <tr> <td>Specification</td> <td>M27*2</td> </tr> <tr> <td>Temperature Range</td> <td>-20°C~+80°C</td> </tr> <tr> <td>Hydraulic resistance</td> <td>31.5MPa</td> </tr> <tr> <td>Protection provided by enclosures</td> <td>IP65</td> </tr> </table>				Type	IW9-03-01	Specification	M27*2	Temperature Range	-20°C~+80°C	Hydraulic resistance	31.5MPa	Protection provided by enclosures	IP65
Type	IW9-03-01												
Specification	M27*2												
Temperature Range	-20°C~+80°C												
Hydraulic resistance	31.5MPa												
Protection provided by enclosures	IP65												
<p><b>Related products</b></p>													
<p><b>Inquiry</b></p> <p>Email:<a href="mailto:aykd_scb@126.com">aykd_scb@126.com</a></p> <p>Name: <input type="text"/></p> <p>* E-mail: <input type="text"/></p> <p>* Content: <input type="text"/></p> <p><a href="#">Send A Message</a></p>													

Prev Article: GWEF50-015

Next Article: GWEF45-004

### Our News

Anyang City Vice Mayor Wang Xinwei  
 My company was named the  
 Anyang City Vice Mayor Du Xinjun line

### About KaiDi

KAI Di Introduction  
 KAI Di Sketch  
 KAI Di Culture  
 KAI Di Honors  
 KAI Di Certification  
 Download

### Leave A Message

Name:

E-mail:

Content:

[Send A Message](#)

### Company Information

High-tech Development Zone, Anyang City,  
 Henan,China  
 Tel:+86-372-2595077/2595078/2595088  
 Email:[aykd\\_scb@126.com](mailto:aykd_scb@126.com)

