



ZC36 Cartridge-type

Engineering environment with an electromagnet is basically a pilot system for a variety of open-electromechanical conversion device as a hydraulic valve or proportional valve power components. High degree of protection, there are several forms of lead type, such as male connector. This series of products for the device to work in harsh outdoor environments, such as excavators, loaders and other.

✉ aykd_scb@126.com

☎ +86-372-2595077/2595078/2595088

Free Live Chat

Leave Message

Products

- ✦ Screw Proportional Solenoid
- ✦ Bolt Proportional Solenoid
- ✦ Servo Proportional Solenoid
- ✦ Rexroth Switch Solenoid
- ✦ Yuken Switch Solenoid
- ✦ Vickers Switch Solenoid
- ✦ Explosion-Proof Solenoid
- ✦ Waterproof Solenoid
- ✦ Position Sensor
- ✦ Displacement Transducer
- ✦ Cartridge Solenoid
- ✦ Latest Research

Quality Assurance

- ✦ Processing Equipment
- ✦ Testing Equipment
- ✦ Quality Control

Contact us

Tel: +86-372-2595077/2595078
/2595088

Fax:

Email: aykd_scb@126.com

Address: High-tech Development Zone,
Anyang City, Henan, China



Description

Parameters

Related products

Inquiry

Description

Uses:

Engineering environment with an electromagnet is basically a pilot system for a variety of open-electromechanical conversion device as a hydraulic valve or proportional valve power components. High degree of protection, there are several forms of lead type, such as male connector. This series of products for the device to work in harsh outdoor environments, such as excavators, loaders and other.

Parameters

The main technical parameters:

Type	ZC36L-S-A/ZC36L-S-ALW
Specification	Φ36.3mm
Effective Stroke	2.7mm
Rated Force	20N
Voltage Specifications	DC12、24V AC115、230V
Protection provided by enclosures	IP65/67

Related products

Inquiry

Email: aykd_scb@126.com

Name:

* E-mail:

* Content:

Send A Message